## AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings of claims in the application:

## LISTING OF CLAIMS:

Claims 1-18 (cancelled).

19. (new) A urine collection device (1) for attachment to a pump (25) and for a user in a supine, or reclined position, said device including:-

an open-mouthed container (2) having a rim (3) around the mouth for being urged in use to seat generally around the periphery of the urine discharge region to receive urine discharged from the urethra,

the container (2) being adapted to fit between the legs of a user in a supine or reclined position,

the container (2) having at its lower part a reservoir basin (10) in which fluid may collect in use when the container (2) is applied to a user in a supine or reclined position, and

an outlet (9) in the lower part of the reservoir basin (10) through which urine may be drawn from the container,

characterised in that the rim (3) has a perineal wall portion
(12) adapted in use to engage edgewise with the perineum to
effect a fluid tight seal, and in that the container is provided
with a vent (36) above the liquid level in the reservoir basin
(10) in use.

- 20. (new) A urine collection device according to Claim
  19 for a female user, wherein said rim (3) is generally of oblate
  curvilinear form, wherein a broader, upper end region of the rim
  (3) is adapted to be seated against the mons pubis (pubic bone
  region), and a narrower lower end region of the rim is adapted to
  be seated against the perineum, in use.
- 21. (new) A urine collection device according to Claim 20, wherein the inner surface region of the container extending inwardly from the lower end region of the rim defines a downwardly-inclined weir surface.
- 22. (new) A urine collection device according to claim 19, wherein the upper and lower ends of the rim (3) define a notional contact plane (XX) which in use lies at between about  $100^{\circ}$  to  $135^{\circ}$  to the horizontal, when the user is reclined or supine.
- 23. (new) A urine collection device according to claim 19, wherein the reservoir basin (10) is defined at least partly by a back wall portion (11) and a bottom wall portion (12) which converge downwardly towards said outlet (9).
- 24. (new) A urine collection device according to Claim 23, wherein the reservoir basin (10) has a capacity of at least 10ml and preferably at least 20ml, when the device is applied to a user in a supine position.
- 25. A urine collection device according to Claim 23, wherein said back wall portion (11) and said bottom wall

portion (10) converge at an angle of between  $90^{\circ}$  and  $120^{\circ}$ , and preferably at about  $106^{\circ}$ .

- 26. (new) A urine collection device according to claim 23 when dependent on Claim 4, wherein said back wall portion (11) lies at an angle of between about  $120^{\circ}$  and  $160^{\circ}$ , and preferably about  $146^{\circ}$  to the notional contact plane.
- 27. (new) A urine collection device according to claim 19, which further includes in the lower region of the mouth at least one weir plate means (15) which extends between opposed portions of the rim (3) and extending into the basin region (10) of the container.
- 28. (new) A urine collection device according to claim
  19 wherein the outlet includes an tubular portion (9) integral
  with the container and having a drain inlet end which is located
  at the lowermost portion of the reservoir basin (10), and which
  extends upwardly to terminate in a drain outlet end.
- 29. (new) A urine collection device according to claim 19, wherein the rim (3) has an inturned resiliently deformable lip extending around a part thereof for seating against the user's body and providing an internal peripheral gutter.
- 30. (new) A urine collection device according to claim 19, wherein said vent (36) includes a breather tube (37) disposed generally vertically, the upper end of said tube being located to the exterior of said container, to prevent escape of urine.
  - 31. (new) A urine collection device according to Claim

30, wherein said container is provided with guard surfaces (41) to prevent inadvertent blocking of the upper end of said tube (37) by the hand of the user in use.

- 32. (new) A urine collection system, comprising a urine collection device (1) according to claim 19, a suction pump (25) for applying suction to said device, and a container (43) for receiving urine drawn from said collection device (1) by said suction pump.
- 33. (new) A urine collection system according to Claim 32, wherein said urine collection device (1) has associated therewith a urine sensor and said system is operable on detection of urine by said sensor to start said suction pump (25).
- 34. (new) A urine collection system according to Claim 32 wherein said vent (36) is sized such that, in use, when the urine collection device (1) is applied to the user, and the suction pump (25) operated, a slight negative pressure is present in the inside of the device to aid location and sealing of the device against the user.
- 35. (new) A urine collection device (1) for attachment to a pump (25) and for a user in a supine, or reclined position, said device including:-

an open-mouthed container (2) having a rim (3) around the mouth for being urged in use to seat generally around the periphery of the urine discharge region to receive urine discharged from the urethra,

the container (2) being adapted to fit between the legs of a user in a supine or reclined position,

the container (2) having at its lower part a reservoir basin (10) in which fluid may collect in use when the container (2) is applied to a user in a supine or reclined position, and

an outlet (9) in the lower part of the reservoir basin (10) through which urine may be drawn from the container, characterised in that said reservoir is defined at least partly by a back wall portion (11) and a bottom wall portion (12) which converge towards said outlet (9), and in that said back wall portion (11) lies at an angle of between 90° and 120° to a notional contact plane (XX) defined by the upper and lower ends of said rim (3).